

Scissor Lift

Used Scissor Lift Escondido - The industrial equipment that utilizes crisscrossed steel linked arms is scissor lifts. These machines feature an “X” support system to accommodate vertical lifting at various heights. Workers use a sizeable rectangle platform that is secured to the top of the lifting apparatus. To maintain operator safety, there are support railings at the top of the platform. The scissor lift has a low profile to maintain stability on hard, compact surfaces like concrete. Scissor lifts can use an electric motor or a combustion engine to transport and lift the machine. The lift function operates on a vertical plane only. In order for the operator to transport the lift horizontally, they will have to reposition the lift itself. Rough terrain and regular lift models rely on the same lifting technology to maneuver the lifting components. The rough terrain units are designed for driving on gravel and uneven surfaces. Higher ground clearance and oversized all-terrain tires enable these machines to travel to tricky locations. Some scissor lifts have 4WD to travel through difficult and muddy locations. Thanks to the higher center of gravity lower lifting heights are available. These machines can be intimidating if you have never been on one or operated one previously. Images of swaying in the wind and being precariously balanced may come to mind. Feel secure knowing you will not feel the lift even moving and you will be in a stable position. Numerous safety tests need to be completed prior to being capable of being sold. It is natural to feel uncomfortable if you are new to this type of equipment. Maintain safety procedures at all times. There are many different kinds of electric scissor lift models to choose from, depending on what you will be using it for. The scissor lift model you will need will largely depend on the types of jobs you will need to do. Key factors to consider include how high you will need to reach and the types of loads you will be moving. Extreme heights can be attained by different models depending on your specific application. Smaller models are commonly used for interior applications including warehouses and freight or factory settings. If you do not need the highest capacity model, there is no need to choose the largest unit available. Optional railings and platforms are available on electrical scissor lifts to provide maximum safety. These machines are designed to be reliable and safe. Many safety inspections and specifications need to be maintained in order for these industrial machines to be available for sale. Scissor lifts enable us to finish tasks that normally are inaccessible or unreachable otherwise. These machines are situated in place before elevating vertically. The operator needs to move the unit into the correct position before engaging the lift. There are a variety of safety features incorporated into the design. Safety is accomplished by following operational guidelines. Scissor lifts offer a secure basket workspace making many tasks much safer than trying to complete while dangling off of a ladder or scaffolding. Most scissor lifts rely on internally mounted batteries within the lifts’ base for power. After working an extensive shift or for prolonged periods of time, charging is necessary. Batteries may be changed every 12 hours or charged many times throughout the day. To charge the scissor lift, the operator parks it close to an electrical outlet within a well-ventilated location. The emergency shut-off switch is engaged upon parking to prevent other operators from driving off while plugged in. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. The battery charger is commonly located on the right side of the lift on the base. Many older models may feature the battery charger mounted on the back of the scissor lift. The charger for the machine is plugged into the AC extension cord within a well-ventilated area and the extension cord plugs into an electrical outlet. The length of the electrical cord on the battery charger needs to be short to prevent damage or running over it. There is a high possibility of danger if the extension cord dropped out of the battery charger while the machine is in operation. After the scissor lift plugs in to charge, all of the lights should become lit up. Once the unit is plugged in, the batteries automatically start to charge. The battery lights will switch to green once complete charging has occurred and the charger will shut off. Older scissor lift models rely on a meter to show whether zero volts have been attained after complete charging has occurred. This type of charger

automatically shuts down as well once charging is done. The machine is ready to tackle another shift once the batteries are fully charged. It is common for warehouses and certain businesses to keep batteries charging around the clock to allow the scissor lift to operate 24 hours a day.